

Crystal OSCILLATOR

2.5 X2. 0MM Surface Mount Package



Approved by:

Checked by:

Issued by:

SPECIFICATION

P/N: 2N32768KDC0XGJM

深圳市晶科鑫实业有限公司
SHENZHEN CRYSTAL TECHNOLOGY INDUSTRIAL CO., LTD.

Tel: 86-755-88352809
E-mail: sjksale@126.com

Fax: 86-755-88353718
URL: [Http://www.q-crystal.com](http://www.q-crystal.com)

Crystal OSCILLATOR

2.5 X2. 0MM Surface Mount Package

FEATURE

- Compact and thin ceramic package with metalized surface mounting and automatically loaded
- Reflow solder is possible
- Lower noise and current with reduced power consumption
- Built-in C-MOS IC with tri-state function
- 1.8~ 3.3V supply model available


ELECTRICAL SPECIFICATIONS

Parameters	Condition\Model	
Fan Out Type		HCMOS
Supply Voltage		1.8~3.3V
Frequency		32.768KHz
Operating Temperature		-40℃ ~ +85℃
Input Current	Frequency Range	70uA max
Frequency Stability	All Conditions	±25ppm
Symmetry	AT 1/2 Vdd	45/55%
Output Voltage	Vol(max)	10% Vdd
	VoH(min)	90% Vdd
Rise/Fall Time	AT 0.1Vdd~0.9Vdd	20ns Max
Driving Ability	CMOS load max	15pF
Start-up Time	Load RANGE	10ms max
E/D Function	#1 OPEN	PIN #3 ACTIVE
	#1 >=70%Vdd	PIN #3 ACTIVE
	#1 <=30%Vdd	PIN #3 HighZ
PAD Connection		PIN#1 E/D PIN#3 OUT
		PIN#2 GND PIN#4 Vdd

Reflow Soldering Profile

Total Time: 200 sec. Max.

Solder Melting Point :220 ℃




The design, manufacturing process, and specifications of this device are subject to change without notice.


Crystal OSCILLATOR

2.5 X2.0MM Surface Mount Package

Dimension



Recommended Solder Pad Layout




All dimensions are in millimeters.

Pin Connections

#1 E/D #3 Output
#2 GND #4 VDD

Waveform Conditions




The design, manufacturing process, and specifications of this device are subject to change without notice.

Crystal OSCILLATOR

2.5 X2. 0MM Surface Mount Package






Tape Dimension



DIMENSIONS	A	B	C	D	E	F	G	H	
	1.15	2.70	2.25	4.00	8.00	4.00	1.55	1.75	(UNIT:mm)
	±0.05	±0.05	±0.05	±0.10	±0.20	±0.10	±0.05	±0.10	

REMARK :



DIMENSIONS	L	L1	W	W1	
	180	60	11.4	9	Standard Reel Quantity is 3,000 pcs per reel
	0/-3	+1/0	±0.1	±0.3	(UNIT:mm)