

Quartz Crystal

SEAM SEALED CERAMIC 5 X 3.2mm Surface Mount Package



Approved by:

Checked by:

Issued by:

SPECIFICATION

P/N: 7I400000CC01MBL

深圳市晶科鑫实业有限公司
SHENZHEN CRYSTAL TECHNOLOGY INDUSTRIAL CO., LTD.

Tel: 86-755-88352809
E-mail: sjksale@126.com

Fax: 86-755-88353718
URL: [Http://www.q-crystal.com](http://www.q-crystal.com)

Quartz Crystal



SEAM SEALED CERAMIC 5 X 3.2mm Surface Mount Package

FEATURE

- Ultra thin, thickness 1.0mm
- Leadless type
- High precision characteristic covering up to high frequency range
- Automatic mounting
- Embossed tapping specification
- Suitable for Reflow soldering

APPLICATIONS


- Ideally suited designed for disc drives, NB, PCs and hand-held electronic products

ELECTRICAL SPECIFICATIONS

Output Frequency Range	40.000MHz
Mode	Fundamental/ AT Cut
Frequency Tolerance (at 25°C)	±9ppm
Frequency Stability Over Operating Temperature Characteristics	±10ppm
Operable Temperature Range	-40 °C to +85 °C
Storage Temperature Range	-55 °C to +105 °C
Shunt Capacitance (C ₀)	5.0 pF Max
Driver Level (Typical)	100μW
Load Capacitance (C _L)	20 pF
Equivalent Series Resistance ESR	30Ω
Aging @25°C 1 st year (Max)	±3ppm/year
Shock Resistance	Drop test of 3 times on 2mm stainless plate from 75cm height

REMARK: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. PLEASE CONFIRM WITH OUR SALES ENGINEER.

Dimension



The design, manufacturing process, and specifications of this device are subject to change without notice.

Quartz Crystal


SEAM SEALED CERAMIC 5 X 3.2mm Surface Mount Package




Reflow Condition

Total Time: 200 sec. Max.


Solder Melting Point :220 °C



Reference Land Pattern



PACKING



The design, manufacturing process, and specifications of this device are subject to change without notice.