

Quartz Crystal

SEAM SEALED CERAMIC 6 X 3.5MM SMD TYPE



Approved by:

Checked by:

Issued by:

SPECIFICATION

P/N: 6G250000B002GJM

深圳市晶科鑫实业有限公司
SHENZHEN CRYSTAL TECHNOLOGY INDUSTRIAL CO., LTD.

Tel: 86-755-88352809
E-mail: sjksale@126.com

Fax: 86-755-88353718
URL: [Http://www.q-crystal.com](http://www.q-crystal.com)

Quartz Crystal

SEAM SEALED CERAMIC 6 X 3.5MM SMD TYPE



FEATURE


- Ultra thin, thickness 1.0mm
- Leadless type
- High precision characteristic covering up to high frequency range
- Automatic mounting
- Embossed tapping specification
- Suitable for solder reflow

ELECTRICAL SPECIFICATIONS

Output Frequency Range	25.000 MHz
Mode	Fundamental
Frequency Tolerance (at 25°C)	±20ppm
Frequency Stability Over Operating Temperature Characteristics	±20ppm
Storage Temperature Range	-40°C ~+85°C
Operating Temperature Range	-20°C ~+70°C
Shunt Capacitance (C ₀)	5.0 pF Max
Driver Level (Typical)	100μW
Load Capacitance (C _L)	18 pF
Equivalent Series Resistance ESR (Ω)	50Ω Max
Aging @25°C 1 st year (Max)	±3ppm/year
Shock Resistance	Drop test of 3 times on 2mm stainless plate from 75cm height

REMARK: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. PLEASE CONFIRM WITH OUR SALES ENGINEER.


Dimension



SEAM SEALED CERAMIC 6 X 3.5MM SMD TYPE




Reference Land Pattern




Reflow Condition

Total Time: 200 sec. Max.

Solder Melting Point :220 °C



PACKING



The design, manufacturing process, and specifications of this device are subject to change without notice.

Page 3 of 3