

Crystal OSCILLATOR

7.0 X5.0MM Surface Mount Package



Approved by:

Checked by:

Issued by:

SPECIFICATION

P/N: 6N0400000002MBL

深圳市晶科鑫实业有限公司
SHENZHEN CRYSTAL TECHNOLOGY INDUSTRIAL CO., LTD.

Tel: 86-755-88352809
E-mail: sjksale@126.com

Fax: 86-755-88353718
URL: [Http://www.q-crystal.com](http://www.q-crystal.com)

Crystal OSCILLATOR

7.0 X5.0MM Surface Mount Package



FEATURE

- Broad frequency ranges from 1.00MHz to 150MHz
- Compact and thin ceramic package with metalized surface mounting and automatically loaded
- Reflow solder is possible
- Lower noise and current with reduced power consumption
- Built-in C-MOS IC with tri-state function
- 5V and 3.3V supply model available


ELECTRICAL SPECIFICATIONS

Parameters	Condition	6N
Fan Out Type		HCMOS
Supply Voltage		5.0V
Frequency		4.000MHz
Operating Temperature		-20°C-70°C
Input Current	Frequency Range	10mA max
Frequency Stability	All Conditions	±100ppm
Symmetry	AT 1/2 Vdd	45/55%
Output Voltage	Vol(max)	10%Vdd
	VoH(min)	90%Vdd
Rise/Fall Time	AT 0.1Vdd~0.9Vdd	10ns Max
Driving Ability	CMOS load max	50pF
Start-up Time	Load RANGE	10ms max
E/D Function	#1 OPEN	PIN #3 ACTIVE
	#1 >=70%Vdd	PIN #3 ACTIVE
	#1 <=30%Vdd	PIN #3 HighZ
PAD Connection		PIN#1 E/D
		PIN#2 GND
		PIN#3 OUT
		PIN#4 Vdd

Reflow Soldering Profile

Total Time: 200 sec. Max.

Solder Melting Point :220 °C




The design, manufacturing process, and specifications of this device are subject to change without notice.

Crystal OSCILLATOR



7.0 X5.0MM Surface Mount Package



DIMENSIONS (UNIT: mm)




Pad Function:
1:ENABLE CONTROL
2:GND
3:OUT
4:VDD




Suggested Layout

PACKING



DIMENSIONS	A	B	C	D	E	F	G	H	(UNIT : mm)
	2.00	7.90	5.45	8.00	16.00	4.00	1.50	1.75	



DIMENSIONS	L	L1	W	W1	pcs / Reel (UNIT : mm)
	180	13	20.5	16	Standard Reel Quantity is 1,000 pcs per reel