

Series 6H

GLASS SEALED CERAMIC 8 X 4.5MM



Approved by:

Checked by:

Issued by:

SPECIFICATION

P/N: 6H0921600C05MBL

深圳市晶科鑫实业有限公司

SHENZHEN CRYSTAL TECHNOLOGY INDUSTRIAL CO., LTD.

Tel: 86-755-88352809

E-mail: sjksale@126.com

Fax: 86-755-88353718

URL: [Http://www.q-crystal.com](http://www.q-crystal.com)

The design, manufacturing process, and specifications of this device are subject to change without notice.

Page 1 of 3

Series 6H

GLASS SEALED CERAMIC 8 X 4.5MM



FEATURE

- Leadless type.
- Automatic mounting.
- Rugged AT-cut crystal construction
- Suitable for solder reflow.
- Available on tape and reel, 1000pcs per reel

APPLICATIONS


Ideally suited designed for disc drives, NB, PCs and hand-held electronic products

ELECTRICAL SPECIFICATIONS

Output Frequency Range	9.216MHz
Mode	Fundamental/AT
Frequency Tolerance (at 25°C)	±30ppm
Frequency Stability Over Operating Temperature Characteristics	±50ppm
Storage Temperature Range	-55 °C to +105 °C
Operable Temperature Range	-40 °C to +85 °C
Shunt Capacitance (C0)	5.0 pF Max
Driver Level (Typical)	10μW
Load Capacitance (CL)	12 pF
Equivalent Series Resistance ESR (Ω)	80 Ohms
Aging @25°C 1 st year (Max)	±5ppm/year
Shock Resistance	Drop test of 3 times on 2mm stainless plate from 75cm height

REMARK: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. PLEASE CONFIRM WITH OUR SALES ENGINEER.

DIMENSIONS (Unit: mm)




Series 6H


GLASS SEALED CERAMIC 8 X 4.5MM



Reference Land pattern (Typical)



Reflow Condition (Example)



Packing

