

CERAMIC RESONATOR

ZTT Series with Built-IN Capacitor



Approved by:

Checked by:

Issued by:

SPECIFICATION

P/N: ZTTCR4.91MGE39PGJM

深圳市晶科鑫实业有限公司
SHENZHEN CRYSTAL TECHNOLOGY INDUSTRIAL CO., LTD.

Tel: 86-755-88352809
E-mail: sjksale@126.com

Fax: 86-755-88353718
URL: [Http://www.q-crystal.com](http://www.q-crystal.com)

CERAMIC RESONATOR

ZTT Series with Built-IN Capacitor



1. SCOPE

This specification shall cover the characteristics of the surface mount ceramic resonator with 4.91MHz.

2. CUSTOMER NO:

3. FACTORY NO: ZTTCR4.91MGE39PGJM

4. ELECTRICAL CHARACTERISTICS

No	Item	Requirements
4.1	Oscillation Frequency (Fosc)	4.91MHz
4.2	Resonant Impedance (Ro)	60Ω
4.3	Temperature Coefficient of Oscillation Frequency	±0.5% max
4.4	Withstanding Voltage	100VDC 10 Seconds
4.5	Rating Voltage (1) D.C. Voltage (2) A.C. Voltage	6 V.D.C. 15 Vpp.
4.6	Insulation Resistance	100M Ω min.(at 10VDC)
4.7	Operating Temperature	-40℃ to +125℃
4.8	Storage Temperature	-55℃ to +125℃
4.9	Aging Rate (Fosc)	±0.3% max (10 year)
4.10	C1C2	39pf±20%

5. MEASUREMENT

5.1 Measurement Condition

The reference temperature shall be 25℃±2℃.The measurement shall be performed at the temperature range of 5℃ to 35℃ unless otherwise the result is doubtful.

5.2 Measurement Circuit and Equipment

Oscillating frequency shall be measured by the standard test Circuit.


Resonant impedance shall be measured by HP8751A Network Analyzer.

CERAMIC RESONATOR

ZTT Series with Built-IN Capacitor



6. DIMENSION



#	Pin #
1	Input
2	Ground
3	Output

*, EIAJ MONTHLY CODE